

4730 Mechanics 3

1	(i) $[0.5(v_x - 5) = -3.5, 0.5(v_y - 0) = 2.4]$ Component of velocity in x-direction is -2ms^{-1} Component of velocity in y-direction is 4.8ms^{-1} Speed is 5.2ms^{-1}	M1 A1 A1 A1	4	For using $I = m(v - u)$ in x or y direction AG
	SR For candidates who obtain the speed without finding the required components of velocity (max 2/4) Components of momentum after impact are -1 and 2.4 Ns Hence magnitude of momentum is 2.6 Ns and required speed is $2.6/0.5 = 5.2\text{ms}^{-1}$	B1 B1		
	(ii) Component is -2.4Ns	M1 A1	2	For using $I_y = m(0 - v_y)$ or $I_y = -y\text{-component of } 1^{\text{st}} \text{ impulse}$
2	(i) $50 \times 1 \sin \beta = 75 \times 2 \cos \beta$ $\tan \beta = 3$	M1 A1 A1	3	For 2 term equation, each term representing a relevant moment AG
	(ii) Horizontal force is 75N Vertical force is 50N	B1 B1	2	
	(iii) For not more than one error in $W \times 1 \sin \alpha + 50(2 \sin \alpha + 1 \sin \beta) =$ $75(2 \cos \alpha + 2 \cos \beta)$ or $W \times 1 \sin \alpha +$ $50 \times 2 \sin \alpha = 75 \times 2 \cos \alpha$ $0.6W + 107.4 \dots = 167.4 \dots$ or $0.6W + 60 = 120$ $W = 100$	M1 A1 A1 A1	4	For taking moments about A for the whole or for AB only Where $\tan \alpha = 0.75$
3	(i) $6 \times 4 - 3 \times 8 = 6a + 3b$ $(0 = 2a + b)$ $(4 + 8)e = b - a$ $(12e = b - a)$ Component is $4e \text{ ms}^{-1}$ to the left	M1 A1 M1 A1 A1	5	For using the principle of conservation of momentum in the i direction For using NEL 'to the left' may be implied by $a = -4e$ and arrow in diagram
	(ii) $b = 8e \text{ ms}^{-1}$ $(8e)^2 = (4e)^2 + v^2$ $v = 4$	B1ft M1 A1ft A1	4	ft $b = -2a$ or $b = a + 12e$ For using 'j' component of A's velocity remains unchanged' ft $b^2 = a^2 + v^2$
4	(i) $[mg - 0.49mv = ma]$ $mv \frac{dv}{dx} = mg - 0.49mv$ $\left[\frac{v (dv / dx)}{g - 0.49v} = 1 \right]$ $\left[\frac{v}{9.8 - 0.49v} \equiv \frac{-1}{0.49} \left(\frac{(9.8 - 0.49v) - 9.8}{9.8 - 0.49v} \right) \right]$ $\left(\frac{20}{20 - v} - 1 \right) \frac{dv}{dx} = 0.49$	M1 A1 M1 M1 A1	5	For using Newton's second law For relevant manipulation For synthetic division of v by $g - 0.49v$, or equivalent AG
	(ii) $\int \frac{20}{20 - v} dv = -20 \ln(20 - v)$ $-20 \ln(20 - v) - v = 0.49x$ (+C) [-20 ln20 = C] $x = 40.8(\ln 20 - \ln(20 - v)) - 2.04v$	M1 B1 A1ft M1 A1	5	For separating the variables and integrating For using $v = 0$ when $x = 0$ Accept any correct form

5	(i) $mg\sin 30^\circ = 0.75mgx/1.2$ Extension is 0.8m	M1 A1 A1	3	AG For using Newton's second law with $a = 0$
	(ii) PE loss = $mg(1.2 + 0.8)\sin 30^\circ$ (mg) EE gain = $0.75mg(0.8)^2/(2 \times 1.2)$ (0.2mg) [$\frac{1}{2}mv^2 = mg - 0.2mg$] Maximum speed is 3.96ms^{-1}	B1 B1 M1 A1	4	For an equation with terms representing PE, KE and EE in linear combination
	(iii) PE loss = $mg(1.2 + x)\sin 30^\circ$ or $mgd\sin 30^\circ$ EE gain = $0.75mgx^2/(2 \times 1.2)$ or $0.75mg(d - 1.2)^2/(2 \times 1.2)$ [$x^2 - 1.6x - 1.92 = 0$, $d^2 - 4d + 1.44 = 0$] Displacement is 3.6m	B1ft B1ft M1 A1	4	ft with x or d - 1.2 replacing 0.8 in (ii) ft with x or d - 1.2 replacing 0.8 in (ii) For using PE loss = EE gain to obtain a 3 term quadratic in x or d
Alternative for parts (ii) and (iii) for candidates who use Newton's second law and $a = v \, dv/dx$: In the following x, y and z represent displacement from equil. pos ⁿ , extension, and distance OP respectively.				
	[$mv \, dv/dx = mg\sin 30^\circ - 0.75mg(0.8 + x)/1.2$, $mv \, dv/dy = mg\sin 30^\circ - 0.75mgy/1.2$, $mv \, dv/dz = mg\sin 30^\circ - 0.75mg(z - 1.2)/1.2$] $v^2/2 = -5gx^2/16 + C$ or $v^2/2 = gy/2 - 5gy^2/16 + C$ or $v^2/2 = 5gz/4 - 5gz^2/16 + C$ [$C = 0.6g + 5g(-0.8)^2/16$ or $C = 0.6g$ or $C = 0.6g - 5g(1.2/4) + 5g(1.2)^2/16$ $v^2 = (-5x^2/8 + 1.6)g$ or $v^2 = (y - 5y^2/8 + 1.2)g$ or $v^2 = (5z/2 - 5z^2/8 - 0.9)g$]	M1 A1 M1 A1		For using N2 with $a = v \, dv/dx$ For using $v^2(-0.8)$ or $v^2(0)$ or $v^2(1.2) = 2(g \sin 30^\circ)1.2$ as appropriate
	(ii) [$v_{\max}^2 = 1.6g$ or $0.8g - 0.4g + 1.2g$ or $5g - 2.5g - 0.9g$] Maximum speed is 3.96ms^{-1}	M1 A1		For using $v_{\max}^2 = v^2(0)$ or $v^2(0.8)$ or $v^2(2)$ as appropriate
	(iii) [$5x^2 - 12.8 = 0 \rightarrow x = 1.6$, $5y^2 - 8y - 9.6 = 0 \rightarrow y = 2.4$, $5z^2 - 20z + 7.2 = 0 \rightarrow z = 3.6$] Displacement is 3.6m	M1 A1	8	For solving $v = 0$
Alternative for parts (ii) and (iii) for candidates who use Newton's second law and SHM analysis.				
	[$m\ddot{x} = mg\sin 30^\circ - 0.75mg(0.8 + x)/1.2 \rightarrow \ddot{x} = -\omega^2x$; $v^2 = \omega^2(a^2 - x^2)$] $v^2 = 5g(a^2 - x^2)/8$	M1 A1 M1		For using N2 with $v^2 = \omega^2(a^2 - x^2)$ For using $v^2(-0.8) = 2(g\sin 30^\circ)1.2$
	$v^2 = 5g(2.56 - x^2)/8$ (ii) [$v_{\max}^2 = 5g \times 2.56 \div 8$] Maximum speed is 3.96ms^{-1}	A1 M1 A1		For using $v_{\max}^2 = v^2(0)$
	(iii) [$2.56 - x^2 = 0 \rightarrow x = 1.6$] Displacement is 3.6m	M1 A1		For solving $v = 0$

4730

Mark Scheme

January 2008

6	(i) $[\frac{1}{2}m7^2 = \frac{1}{2}mv^2 + 2mg]$ Speed is 3.13ms^{-1} $[T = mv^2/r]$ Tension is 1.96N	M1 A1 M1 A1ft	4	For using the principle of conservation of energy For using Newton's second law horizontally and $a = v^2/r$
	(ii) $[T - mg\cos\theta = mv^2/r]$ $v^2 = -2g\cos\theta$ $\frac{1}{2}m7^2 = \frac{1}{2}mv^2 + mg(2 - 2\cos\theta)$ $[-2g\cos\theta = 49 - 4g + 4g\cos\theta]$ $6g\cos\theta = -9.8$ $\theta = 99.6$	M1 M1 A1 M1 A1 M1 A1 A1		8
Alternative for candidates who eliminate v^2 before using $T = 0$.				
7	(ii) $[T - mg\cos\theta = mv^2/r]$ $\frac{1}{2}m7^2 = \frac{1}{2}mv^2 + mg(2 - 2\cos\theta)$ $[T - mg\cos\theta = m(49 - 4g + 4g\cos\theta)2]$ $-2g\cos\theta = 49 - 4g + 4g\cos\theta$ $6g\cos\theta = -9.8$ $\theta = 99.6$	M1 M1 A1 M1 M1 A1ft A1 A1	8	For using Newton's second law radially For using the principle of conservation of energy For eliminating v^2 For using $T = 0$ (may be implied) ft error in energy equation May be implied by answer
	(i) $T = 4mg(4 + x - 3.2)/3.2$ $[ma = mg - 4mg(0.8 + x)/3.2]$ $4\ddot{x} = -49x$	B1 M1 A1		3
7	(ii) Amplitude is 0.8m Period is $2\pi / \omega$ s where $\omega^2 = 49/4$ Slack at intervals of 1.8s	B1 B1 M1 A1	4	(from $4 + A = 4.8$) String is instantaneously slack when shortest ($4 - A = 3.2 = L$). Thus required interval length = period. AG
	(iii) $[ma = -mg\sin\theta]$ $mL\ddot{\theta} = -mg\sin\theta$ For using $\sin\theta \approx \theta$ for small angles and obtaining $\ddot{\theta} \approx -(g/L)\theta$	M1 A1 A1		3
7	(iv) $[\theta = 0.08\cos(3.5 \times 0.25)] (= 0.05127..)$ $[\dot{\theta} = -3.5(0.08)\sin(3.5 \times 0.25),$ $\dot{\theta}^2 = 12.25(0.08^2 - 0.05127..^2)]$ $\dot{\theta} = \mp 0.215$ $[v = 0.215 \times 9.8/12.25]$ Speed is 0.172ms^{-1}	M1 M1 A1 M1 A1	5	For using $\theta = \omega\cos\omega t$ where $\omega^2 = 12.25$ (may be implied by $\dot{\theta} = -\omega\sin\omega t$) For differentiating $\theta = \omega\cos\omega t$ and using $\dot{\theta}$ or for using $\dot{\theta}^2 = \omega^2(\theta_0^2 - \theta^2)$ where $\omega^2 = 12.25$ May be implied by final answer For using $v = L\dot{\theta}$ and $L = g/\omega^2$